03.31.2025 **JOURNAL OF**

African Sustainable Development (JASD) Vol. 7 No. 2

ENERGY VALUE AND RELATED PROPERTIES OF *Deterium microcarpum* (*sweet detar, sweet dattock or tallow tree*) GUILL & PERR

WAKILI, ADAMU

Tetfund Centre of Excellence for Integrated Farming Systems, Federal Polytechnic, PMB 0231 Bauchi, Bauchi State – Nigeria

Corresponding Author: adamuwakili1@gmail.com

DOI Link: https://doi.org/10.70382/ bejasd.v7i2.007

ABSTRACT

A fresh wood sample of *Detarium microcarpum* Guill & Perr was taken from Buskuri open Savanna woodland and tested for moisture content, calorific value, combustion rate and its coppicing ability measured. The study shows that the moisture content at the time of energy determination was found to be 4.75 percent and the calorific value of 15.32 Mj/Kg was recorded. The results also reveals that in eight minutes, the temperature of the wood sample reached 520°C and temperature above 100°C was retained for a period of 28minutes. The species was found to coppice at the rate of 100cm per annum. An urgent need to stop cutting *Detarium microcarpum* for fuel wood and the need for advance research on

Introduction

Forest provides the bulk of domestic energy for cooking and space heating among the rural communities in Nigeria (Akpan *et al*., 2005). This is due to its availability, accessibility, affordability and simplicity in utilization. Other forms of energy of fossil origin are beyond economic capability of the majority of people living in rural areas. In addition, the supply of such energy is limited and erratic.

Forest in the tropical developing nations are extensively used for grazing, fuel wood collection, cutting

E-ISSN 3026-8575 P-ISSN 3027-1266

the wood properties of the same species for enhanced diversification of utilization were recommended.

Key words: Calorific value-Coppice-Combustion rate-Temperature-Moisture

for medicinal purposes and other numerous subsistence needs by local people even inside protected areas that have been priotized for biodiversity conservation (Kothari *et al*., 1989). The heavy dependence on wood for fuel and timber products has contributed to the accelerated forest and woodland degradation. This is particularly serious where population is dense and with little or no substitute to biofuel as a result of lean financial earnings.

Fuel wood is the dominant energy form throughout Africa and the rest of developing world (Pandey, 2002, and Hall, 1991). The importance of fuel wood in economic development cannot be overemphasized. In Nigeria and in the rural areas in particular, the major energy sources

Fuel wood collection is a common and widely practiced economic activity of the rural dwellers and this was necessitated by the ever increasing demand for fuel wood as a formidable source of energy for household cooking, barbecuing, bakery and blacksmithing industries, fish smoking and oil palm production (Tella et al., 2005).

Presently due to increased loss of floral biodiversity, fuel wood collection is indiscriminate as a result; species of low energy value but of higher pharmaceutical, constructive and conservative values and numerous socio-economic importances are being carelessly removed. This leads to the loss of species of high quality timber and pharmaceutical potentials, and its attendant deforestation that leads to severe environmental degradation. To stop this ecologically ill practice, it is of paramount importance to investigate the energy related attributes of commonly used woody species in order to show case same to the teeming fuel wood users, government and non-governmental organizations within developing nations, so that a choice can

be made in terms of utilization and woodlot establishment and management (Wakili *et al*., 2009).

Energy sources need to be managed for enhanced sustained yield that will guarantee benefits for present and future generation. This is because fuels of fossil origin are depletable in nature and indiscriminate cutting of natural vegetation tends to destroy the quality and quantity of biodiversity and its attendant environmental backwardness. These conditions either in solitary or in association, threatens the survival of mankind. It is of paramount importance therefore to know the right species to cut for a particular usage so that the delicate balance between the ecosystems and its components are maintained.

The aim of this study was to determine a) Energy value (Calorific value), b) Combustion rate and c) Coppicing Ability of *Detarium microcarpum* Guill & Perr. With a view to either encourage its cooption in to woodlot plantation schemes in the tropics or discourage its utility for energy generation because of poor energy related properties.

METHODOLOGY

About the species 'Tallow tree' (*Detarium microcarpum)* Guill & Perr.

Detarium microcarpum Guill & Perr is a tree indigenous to Savanna ecozone of Africa that grows mostly in Burkina Faso, Nigeria and Sudan belonging to the family Fabaceae and sub- family Caesalpinioideae. *Detarium microcarpum* has various economic and health attributes such as antioxidant, Hepatitis C inhibitor and antidiabetic. Seed flour traditionally served as an emulsifying and thickening agent. The two edible parts of *Detarium microcarpum* are pulp and seed. These pulp and seed have an almost identical carbohydrate content (40.2%). Pulp contains protein (2.9-6.1%), lipids (0.7-2.3%) and minerals: magnesium (51-84 $mg.100g^{-1}$), Potassium (1.017 $mg.100^{-1}$) and vitamins (Vitamin C: 4.76- 4.7 $mg.100^{-1}$. Seed also contains proteins (34.5-37.1%), lipids (23%), minerals and vitamins (vitamins C : 9.3- 28.1$mg.100g^{-1}$). Seed

powder exhibits functional properties such as bulk density (0.5-0.9g.cm^{-3}), water absorption capacity (3.5- 11.7 ml.g^{-1}), oil absorption capacity (0.7-3.1ml.g^{-1}), solubility (2-3%), emulation capacity (4.3-4.4%), emulation stability (3.4-3.5%), forming capacity (8.7-8.8cm^3) and foam stability (7.0-9.3cm^3) (Akouloukihi et al,. 2022)

Collection of wood sample

A fresh wood sample of *Detarium microcarpum* was obtained from Buskuri open forest in Bauchi State, Nigeria ($9^0 30^1$ and $12^0\ 30^1$ North of the equator and longitude $8^0 50^1$ and 11^0 east of the green wich meridian). This forest is denuded woodland as a result of excessive cutting for fuel wood. The collection was made in the dry season. The collected sample was tested for moisture, calorific value, combustion rate and its regeneration effort measured.

Determination of Moisture content

The apparatus used for this test were an electric oven (DHD 1901), digital weighing balance, wet and dry bulb thermometers. The wood sample was introduced in to an oven maintained at 105^{0}C for one to four hours until uniform weight was attained (ASTM-D143-82). The moisture was determined using an equation, thus,

$$MC = \frac{A-B}{B} * 100$$

Where MC = Moisture content

A = Original mass of sample

B = Oven dry mass of sample

Determination of Calorific Value

To determine the energy value of the wood sample, a bomb calorimeter (LECO-AC-350) and an electric balance were used in accordance with ASTM-

D143-82. The analysis was conducted at National Metallurgical Centre Jos, Plateau State- Nigeria.

Determination of Combustion Rate

The apparatus used were Pyrometer, Thermocouple and Crucible. The test was conducted in a form of open fire under indoor condition. After ignition, the wood sample was allowed to flame until completely burnt in to ash. 30g of the wood sample was put in to crucible. The sample was ignited using matches and a little kerosene. The temperature of the burning sample was taken at an interval of two minutes until it completely get burnt. This test was conducted at the thermodynamics laboratory, Abubakar Tafawa Balewa University, Bauchi- Nigeria.

Determination of Regeneration Ability of the Species

The natural regeneration ability of the species was measured by observing its stump that gives out coppice shoot under natural condition. An annual average height and number of successful coppice shoot were measured. An average height of the species were obtained by summing of all year old re-growth of five stools of the species and divided by number of the species (stools). The number of the coppice shoot that graduated in to tree size were considered as successful coppice shoot.

RESULTS AND DISCUSSION

Moisture content

The moisture content of *Detarium microcarpum* at the point of energy determination (4.75 percent) was found to be below equilibrium moisture content of 15% (Zobel and Van Bejutenem, 1989). This is because when the fresh sample of the wood was collected, it was splitted there by exposing much of the wood surface to the drying wind and sun. Wood begins to dry out as soon as it is cut and progress through several stages. In the first stage of

drying, free water is lost until fibre saturation point is reached. Drying beyond this point to equilibrium moisture content takes progressively longer, since it involves the removal of bound water. The moisture content at this levels and the rate of drying vary depending on humidity and temperature (Wakili *et al*., 2012). Since even at 25% moisture content, 80% of the content energy will be available for utility (Reyes et al., 1992), drying wood sample to as low as 3.81% will necessitate the release of all the quantum of energy of the wood sample.

Calorific Value

The results of calorific value determination indicates that *Detarium microcarpum* wood sample contains 15.32 Mj/Kg at the time bomb calorimetric analysis, as a result of low moisture the sample was having at the time of the analysis. Moisture content of wood is one of the major determinants of wood's energy for utilization. This is because the higher the moisture content of wood, the lesser the utility energy and the lesser the moisture content of wood the higher the available usable energy.

The energy value obtained is higher than that of *Anogeissus leiocarpus* (23.945Kj/Kg) and *Prosopis africana* (20.925Kj/Kg) at 10.75% and 9.82% moisture, respectfully, as reported by Onuarah,1999. The variation may be as a result of differences in moisture content because moisture affects the production of usable energy when wood is burnt (Zobel and Van Bejutenen, 1989).

However, the energy value obtained in this study is lower than the energy value of some fuel wood tree species reported by Wakili *et al*., 2009 and Wakili and Abdullahi,2020. The former reported the energy value of 16.554Mj/Kg for *Anogeissus leiocarpus* and the later reported energy value of 17.934 Mj/Kg for *Prosopis africana.* The energy value obtained from this study will not provide the needed energy for small and medium enterprises, and homes which are dependent on wood as a source of energy. The energy value of

Detarium microcarpum (16.49Mj/Kg) indicates that much quantity is needed to carry out a heating or cooking exercise and by extension, many trees of the same species must be cut in order to have the required quantum of energy. This will increase the rate of deforestation and its attendant environmental degradation. The valuable money and time needed to address other important issues at the family and community levels are being wasted in acquiring less energy value wood.

Combustion Rate Test

The combustion rate test of *Detarium microcarpum* indicated that in eight minutes the highest temperature of 550^{o}C was reached and which in just two minutes dropped to 400^{o}C and progresses to 100^{o}C in sixteen minutes there after (Table 1). Temperature above boiling point was maintained for a period of 20 minutes and there after the heat drastically dropped. The combustion rate test of *Acacia hebecladoeids* shows that in ten minutes, a peak temperature of 335^{o}C was obtained in 26minutes and dropped to 110^{o}C in 28 minutes, and maintained temperature above 100^{o}C for 25minutes (Wakili *et al*., 2012). Comparatively also, Wakili et al., 2009 reported that *Anogeissus leiocarpus* attained a temperature of 320^{o}C in ten minutes and immediately starts *to* drop. *Detarium microcarpum* attains the highest temperature (550^{o}C) among these tree species but this temperature drops immediately indicating that it will not be suitable for heating operations requiring a sustained heat for longer period of time.

Since many contributors(Chapagain, 2006, Usama, 2007 and Abdullahi *et al*.,2010, Wakili,2024) have reported areas where *Detarium microcarpum* play an important role in solving a variety of socio-economic problems; suitability of its wood for agricultural hand tools handle, forage tree, fruits used for votive offerings, medicinal attributes, construction and conservative values among others, the attention be therefore tailored towards provision of these vital goods and services rather than cutting this species for fuel wood.

Table 1. Combustion rate test of *Detarium microcarpum* Guill & Perr

Time (Minutes)	Temperature (°C)
0	30
2	98
4	210
6	410
8	550
10	400
12	360
14	310
16	290
18	270
20	220
22	200
24	160
26	130
28	100

Coppicing Ability of *Detarium microcarpum Guill & Perr*

The coppicing ability of *Detarium microcarpum* was observed in Buskuri open Savanna woodland by noticing the presence and measuring the height of coppice re growth from the stool of the same species. It was observed that the stool profusely coppice and the coppice shoot can grow at the rate of more than 100cm per annum. This clearly indicates that this species can be used in the establishment of other forms of plantations rather than woodlot. Even though the species is slow growing at sapling stage, if a project is meant to produce forage and fruit trees, this species can be a good candidate and because of its double root system that can adequately support its coppice shoot. *Acacia hebecladoeids was reported to coppice at the rate of 135cm per annum,* Combretum molle 131cm, *Combretum glutinosum 132*cm,

*Pterocarpus erinaceus 175*cm, *Khaya senegalensis 156*cm and *Nauclear latifolia* 180cm (Wakili *et al.*,2012).

Conclusion

Detarium microcarpum have little energy value compared to many fuel wood tree species even though the temperature of the available calories can be maintained for a considerable period of time. This indicated that this species is not suitable for fuel wood but since it was reported that the species plays a vital role in the provision of wood for tool handles, construction, and pharmaceuticals, the species can be managed for these reasons rather than fuel wood.

Recommendations

1. That there is an urgent need to stop cutting *Detarium microcarpum* for fuel wood because of its low energy content.
2. That the species (*Detarium microcarpum*) will be good for timber plantation because of its strong and durable wood.
3. That as an incentive, plantation inputs be made available to all intending plantation developers free of charge by both government and non-governmental organizations.
4. That there is the need for advance research on wood properties of *Detarium microcarpum* for enhanced diversification of utility.

References

Akouboukihi, D.T., Vlad, M., Andriano, J.D., Adriana, P., Fidele, P.T. , Andruta, M., Frederic, H. and Mohamed, M.S (2022). Detarium microcarpum Guill& Perr Fruit Properties, Processing and food uses. A Review. *Biotechno.Agron.Soc.Environ.* **26**(3) 144-154

Akpan,M., Wakili,A. and Akosim,C (2005). Fuel wood Consumption Pattern In Bauchi State: A guide for Energy Planers in Nigeria. *International Journal of Agricultural Sciences, Sciences, Environment and Technology* **5**(11): 70-75

Chapagain, B.P (2006). Characterization of Desert Date (*Balanites aegyptiaca*) Saponins and their Biological activities. Unpublished Ph.D Thesis, Ben-Gurian University of the Negev: 1-5

Hall, O.O (1991). Biomass Energy. *Energy Policy* **19**: 3-11

Kothari, A.,Pande,P., Singh,S. and Variava, D (1989). Management of National Park and Sanctuaries in India: a status report, Delhi India. Indian Institute of Administration

E-ISSN 3026-8575 P-ISSN 3027-1266

Onuarah, E.O (1999). The energy value and related characteristics of twenty two of the Most commonly used fuel wood species of Makurdi L.G.A. and Environs. *Nigerian Journal of Renewable Energy* **7**(1 and 2): 87-90

Pondey, D (2002). Fuel wood studies in India: Myth and reality, Bogor CIFOR

Reyes, G., Brown, S. Chapman, J. and Lugo, A.E (1992). Wood Densities of Tropical Tree spcies General Technical Report50/88 United States Department of Agriculture, Forest Services Southern Forest Experimental station, New Orleans

Tella, I.O., Akpan, M., Ijomah, J.U. and Wakili, A (2015). Fuel wood consumption pattern of the rural communities of Adamawa State, Nigeria. *Journal of Environmental Sciences*. **9**(2):89-96

Usama, A.A.R (2007). Photosynthetic and Leaf Anatomical characteristics of the Drought-Resistance *Balanites aegyptiaca* seedlings. American-Eurasian J. Agric and Environ. Sci. **2**(6):680-688

Wakili, A. and Abdullahi, M.B (2020). Identification of Fuel wood Tree species in Bauchi State *Agriculture, Bussiness and Technology Journal* **8**(2):51-58

Wakili, A., Gani, A.M. and Abdul, S.D(2009). Calorific value and related properties of *Anogeissus Leiocarpus* as one of the most common fuel wood species in Bauchi metropolis. *Journal of Leaque of Researchers in Nigeria* **10** (1): 47-49

Wakili, A., Garba,A., Mato,A. and Kyauta, E.E(2012). Calorific value and related properties of *Acacia hebecladoies* as one of the common fuel wood tree species in Tafawa Balewa metropolis,Tafawa Balewa LGA Bauchi State, Nigeria. *JOLORN* **13**(2):18-24

Wakili, A.(2024). Food Value of Baobab (*Adansonia digitata*) Leaves. *Journal of Agriculture and Environmental Science Research 5(1)* : 209-216

Zobel, B. J. and VanBujitenem, J.P (1989). Wood variation, its causes and control. *Springer Verlag*, Berlin 363pp

E-ISSN 3026-8575 P-ISSN 3027-1266